

City of Lynchburg
Procurement Division
900 Church Street
Lynchburg, Virginia 24504
Telephone No.: (434) 455-3970
Fax No.: (434) 845-0711

**Addendum for Invitation for Bids
E. C. Glass Tennis Court Reconstruction**

14-908

Date: 4/30/14
From: Lisa Moss, Buyer VCA
RE: Addendum No. 1

This Addendum supplements and amends the original Plans and Specifications and shall be taken into account in preparing proposals and shall become a part of the Contract Documents. The Bidder shall indicate receipt of this Addendum and all previously issued Addenda on the Bid Form.

1. Attached below is the Scope of work for this project.

Company Name: _____ *Address:* _____ *Date:* _____

Authorized Signature: _____ *Title:* _____

Print Name: _____ *Telephone No.:* _____

Fax No.: _____

E.C. GLASS TENNIS COURT RECONSTRUCTION 2014

Scope of work

Lynchburg City Schools (LCS) is seeking bids for the reconstruction of twelve (12) asphalt tennis courts located at E. C. Glass High School. LCS is seeking possible multiple award options for the twelve courts broken down into a four (4) court packages. A four (4)-court package, an eight (8)-court package, and a twelve (12)-court package. Starting with the four (4) courts located at the north end of the facility (Bank #1) and proceeding towards the south end (bank # 3). An alternate price is requested for the complete renovation of existing fencing structures to black vinyl coated chain link with black powder coated post or sleeves , new windscreens and there installation.

The court reconstruction shall be awarded based on available funding to accomplish as many reconstructed courts as possible.

A. Demolition & Site Preparation

1. Remove existing fence as necessary to provide vehicle and equipment access to courts. Existing post set in concrete curb may be cut and replaced or re re-welded upon completion. Build construction entrance as necessary to access courts to protect concrete coping around exterior of courts.
2. Remove existing net post their foundations and center strap anchors and dispose of offsite.
3. Remove existing light pole foundations and dispose of offsite.
4. Pulverize and blend existing asphalt surface and underlying base materials to a depth of 8". Remove and dispose of any large unusable material and excessive spoilage off site. Retain concrete curb.
5. Grade blended base materials to a grade of between 0.83% and 1.0%. Compact blended materials with 10-ton vibratory roller to a density of 95% Standard Compaction (ASTM D698).
6. Unstable areas greater than 5 SY. per court will be paid for as an add-on cost at the unit price quoted.

B. Asphalt Surface Installation

1. Install and compact an additional 1" of ABC crushed stone base course using a laser operated motor grader.
2. Tack surface with hot asphalt emulsion, place and compact leveling course, type I19B, to a compacted thickness of 2" and a surface course, type S9.5A to a compacted thickness of 1". Stager asphalt seams for each lift of asphalt. Insure finished surface drains across any surrounding curb or to existing drainage.
3. Reinstall existing court fence at access points.

4. Provide and install net post collars and center strap hooks in concrete. Net post footings should be 24" dia. X 36" deep bell shaped) in accordance with attached specs. Net post to be sleeved in PVC pipe. Dispose of spoils from net post install off site.

C. Court Surfacing

1. After asphalt has cured a minimum of thirty (30) days, flood court with water to identify any low spots or depressions. Depressions in excess of 1/8" after one (1) hour shall be marked in chalk. Patch all marked depression using an acrylic patch binder, then sanded level with surrounding court area.
2. Apply two (2) coats of acrylic resurfacer (Lakold, or approved equal) according to manufacturer's directions.
3. Apply one (1) sand filled coat and one (1) finish coat of Laykold Acrylic Colorcast (or approved equal) according to manufacturer's directions.
Colors: Centers -*DARK BLUE*, Borders - *MEDIUM GREEN* (Laykold color palette)
4. Layout, mask, and hand paint playing lines (2" width) with Laykold Textured White Acrylic Line Paint (or approved equal) in accordance with manufacturer's directions and to USTA specifications.
5. Supply and install four sets (4 sets per court package) new PST-10 net post with internal wind tear dropped shape.
6. Supply and install four (4 per court package) NetGSL Grand Slam tennis nets with double stitch top 6 rows.
7. Clean-up area and dispose of all debris. Leave courts ready for play.

Enclosed documents

1. Subsurface Verification report dated July 1. 2013- Auger probe report of existing asphalt, base stone and shallow soil condition. Hurt & Proffitt Inc.
2. Typical Net Post installation cut sheet.
3. Net Post product information
4. Net product information
5. Windscreen sizing information